

#### COORDINATES COLLECTION



WIDTH 110" (280 CM)

COMPOSITION 100% Polyester

OPENNESS FACTOR N/A

STANDARD ROLL LENGTH 38.29 LY (35m)

WEIGHT 10.32 oz/yd2 (350 g/m2) +/- 5%

THICKNESS 0.0217" (0.55mm) +/- 5%

COLOR FASTNESS TO LIGHT 4 DIN 1SO 105 - BO2; DIN EN 410; DIN EN 13363-1

FIRE CLASSIFICATIONS N/A

ANTI-MICROBIAL N/A

ENVIRONMENTAL REACH

ACOUSTIC PERFORMANCE N/A

CUTTING Ultrasonic

CARE INSTRUCTIONS Do not allow dust to accumulate. Regularly vacuum gently or use compressed

air. Use damp cloth only, do not allow shade to become fully wet. Do not

scrub. Test in inconspicuous area with mild detergent prior to spot cleaning.

















#### COORDINATES COLLECTION



WIDTH 110" (280 CM)

COMPOSITION 100% Polyester

OPENNESS FACTOR N/A

STANDARD ROLL LENGTH 38.29 LY (35m)

WEIGHT 4.72 oz/yd2 (160 g/m2) +/- 5%

THICKNESS 0.016" (0.41mm) +/- 5%

COLOR FASTNESS TO LIGHT 5+ DIN 1SO 105 - B02; DIN EN 410; DIN EN 13363-1

FIRE CLASSIFICATIONS N/A

ANTI-MICROBIAL N/A

ENVIRONMENTAL REACH

ACOUSTIC PERFORMANCE N/A

CUTTING Ultrasonic

CARE INSTRUCTIONS Do not allow dust to accumulate. Regularly vacuum gently or use compressed

air. Use damp cloth only, do not allow shade to become fully wet. Do not

scrub. Test in inconspicuous area with mild detergent prior to spot cleaning.

















#### COORDINATES COLLECTION



WIDTH 114" (290 CM)

COMPOSITION 100% Polyester

OPENNESS FACTOR OPACITY: AS2663.3 Appendix B - NONE

STANDARD ROLL LENGTH 22 LY (20m)

WEIGHT 14.82 oz/yd2 (430 g/m2) +/- 5%

THICKNESS 0.03" (0.76mm) +/- 5%

COLOR FASTNESS TO LIGHT 8 GRADE AS 2001.4.21 (Australian Standard)

FIRE CLASSIFICATIONS AS 1530.3 (Australian Standard)

ANTI-MICROBIAL Bacterial Resistance: N/A; Fungal Resistance: N/A

ENVIRONMENTAL GreenGuard, RoHS-Lead-Free, REACH

ACOUSTIC PERFORMANCE N/A

CUTTING Cold, Ultrasonic, Crush or Laser

CARE INSTRUCTIONS Do not allow dust to accumulate. Regularly vacuum gently or use compressed

air. Use damp cloth only, do not allow shade to become fully wet. Do not

scrub. Test in inconspicuous area with mild detergent prior to spot cleaning.

























#### COORDINATES COLLECTION



WIDTH 118" (299.72 CM)

COMPOSITION 100% Polyester

OPENNESS FACTOR N/A

STANDARD ROLL LENGTH 22 LY (20m)

WEIGHT 5.94 oz/yd2 (200g/m2) +/-5%

THICKNESS 0.025" (0.63mm) +/- 5%

COLOR FASTNESS TO LIGHT 6 GRADE AS 2001.4.21 (Australian Standard)

FIRE CLASSIFICATIONS AS 1530.3 (Australian Standard)

ANTI-MICROBIAL Bacterial Resistance: N/A; Fungal Resistance: N/A

ENVIRONMENTAL GreenGuard, RoHS-Lead-Free, REACH

ACOUSTIC PERFORMANCE N/A

CUTTING Cold, Ultrasonic, Crush or Laser

CARE INSTRUCTIONS Do not allow dust to accumulate. Regularly vacuum gently or use compressed

air. Use damp cloth only, do not allow shade to become fully wet. Do not

scrub. Test in inconspicuous area with mild detergent prior to spot cleaning.

























#### COORDINATES COLLECTION



WIDTH 114" (290 CM)

COMPOSITION 100% Polyester

OPENNESS FACTOR OPACITY: AS2663.3 Appendix B - NONE

STANDARD ROLL LENGTH 22 LY (20m)

WEIGHT 13.9 oz/yd2 (395 g/m2) +/- 5%

THICKNESS 0.29" (0.73mm) +/- 5%

COLOR FASTNESS TO LIGHT 6 GRADE AS 2001.4.21 (Australian Standard)

FIRE CLASSIFICATIONS AS 1530.3 (Australian Standard)

ANTI-MICROBIAL Bacterial Resistance: N/A; Fungal Resistance: N/A

ENVIRONMENTAL GreenGuard, RoHS-Lead-Free, REACH

ACOUSTIC PERFORMANCE N/A

CUTTING Cold, Ultrasonic, Crush or Laser

CARE INSTRUCTIONS Do not allow dust to accumulate. Regularly vacuum gently or use compressed

air. Use damp cloth only, do not allow shade to become fully wet. Do not

scrub. Test in inconspicuous area with mild detergent prior to spot cleaning.

























#### COORDINATES COLLECTION



WIDTH 118" (299.72 CM)

COMPOSITION 100% Polyester

OPENNESS FACTOR N/A

STANDARD ROLL LENGTH 22 LY (20m)

WEIGHT 6.35 oz/yd2 (180g/m2) +/-5%

THICKNESS 0.025" (0.60mm) +/- 5%

COLOR FASTNESS TO LIGHT 6 GRADE AS 2001.4.21 (Australian Standard)

FIRE CLASSIFICATIONS AS 1530.3 (Australian Standard)

ANTI-MICROBIAL Bacterial Resistance: N/A; Fungal Resistance: N/A

ENVIRONMENTAL GreenGuard, RoHS-Lead-Free, REACH

ACOUSTIC PERFORMANCE N/A

CUTTING Cold, Ultrasonic, Crush or Laser

CARE INSTRUCTIONS Do not allow dust to accumulate. Regularly vacuum gently or use compressed

air. Use damp cloth only, do not allow shade to become fully wet. Do not

scrub. Test in inconspicuous area with mild detergent prior to spot cleaning.

























#### COORDINATES COLLECTION



WIDTH 114" (290 CM)

COMPOSITION 100% Polyester

OPENNESS FACTOR OPACITY: AS2663.3 Appendix B - NONE

STANDARD ROLL LENGTH 22 LY (20m)

WEIGHT 12.24 oz/yd2 (415 g/m2) +/- 5%

THICKNESS 0.025" (0.63mm) +/- 5%

COLOR FASTNESS TO LIGHT 6 GRADE AS 2001.4.21 (Australian Standard)

FIRE CLASSIFICATIONS AS 1530.3 (Australian Standard)

ANTI-MICROBIAL Bacterial Resistance: N/A; Fungal Resistance: N/A

ENVIRONMENTAL GreenGuard, RoHS-Lead-Free, REACH

ACOUSTIC PERFORMANCE N/A

CUTTING Cold, Ultrasonic, Crush or Laser

CARE INSTRUCTIONS Do not allow dust to accumulate. Regularly vacuum gently or use compressed

air. Use damp cloth only, do not allow shade to become fully wet. Do not

scrub. Test in inconspicuous area with mild detergent prior to spot cleaning.

























#### COORDINATES COLLECTION



WIDTH 118" (299.72 CM)

COMPOSITION 100% Polyester

OPENNESS FACTOR N/A

STANDARD ROLL LENGTH 22 LY (20m)

WEIGHT 5.64 oz/yd2 (160g/m2) +/-5%

THICKNESS 0.016" (0.40mm) +/- 5%

COLOR FASTNESS TO LIGHT 6 GRADE AS 2001.4.21 (Australian Standard)

FIRE CLASSIFICATIONS AS 1530.3 (Australian Standard)

ANTI-MICROBIAL Bacterial Resistance: N/A; Fungal Resistance: N/A

ENVIRONMENTAL GreenGuard, RoHS-Lead-Free, REACH

ACOUSTIC PERFORMANCE N/A

CUTTING Cold, Ultrasonic, Crush or Laser

CARE INSTRUCTIONS Do not allow dust to accumulate. Regularly vacuum gently or use compressed

air. Use damp cloth only, do not allow shade to become fully wet. Do not

scrub. Test in inconspicuous area with mild detergent prior to spot cleaning.

























#### COORDINATES COLLECTION



WIDTH 118"

COMPOSITION 100% Polyester

STANDARD ROLL LENGTH 33 LY (30m)

WEIGHT 12.52 oz/yd2 (424 g/m2) +/- 5%

THICKNESS 0.026" (0.66mm) +/- 5%

COLOR FASTNESS TO LIGHT 4.5 GRADE (AATCC 16-2003)

FIRE CLASSIFICATIONS CA U.S. Title 19; CAN/ULC-S109-14 Small Flame Test; NFPA701-2019 TM#1;

BS 5867:2008 Part 2:Type B

ANTI-MICROBIAL Bacterial Resistance: ASTM E2180; Fungal Resistance: ASTM G21, ASTM

G22, ECV

ENVIRONMENTAL GreenGuard, RoHS-Lead-Free, OEKO-TEX 100

ACOUSTIC PERFORMANCE N/A

CUTTING Cold, Ultrasonic, Crush or Laser

CARE INSTRUCTIONS Do not allow dust to accumulate. Regularly vacuum gently or use compressed

air. Use damp cloth only, do not allow shade to become fully wet. Do not

scrub. Test in inconspicuous area with mild detergent prior to spot cleaning.





















#### COORDINATES COLLECTION



WIDTH 118"

COMPOSITION 100% Polyester

STANDARD ROLL LENGTH 33 LY (30m)

WEIGHT 6.92 oz/yd2 (234g/m2) +/- 5%

THICKNESS 0.014" (0.36mm) +/- 5%

COLOR FASTNESS TO LIGHT 4.5 GRADE (AATCC 16-2003)

FIRE CLASSIFICATIONS CA U.S. Title 19; CAN/ULC-S109-14 Small Flame Test; NFPA701-2019 TM#1;

BS 5867:2008 Part 2:Type B

ANTI-MICROBIAL Bacterial Resistance: ASTM E2180; Fungal Resistance: ASTM G21, ASTM

G22, ECV

ENVIRONMENTAL GreenGuard, RoHS-Lead-Free, OEKO-TEX 100

ACOUSTIC PERFORMANCE N/A

CUTTING Cold, Ultrasonic, Crush or Laser

CARE INSTRUCTIONS Do not allow dust to accumulate. Regularly vacuum gently or use compressed

air. Use damp cloth only, do not allow shade to become fully wet. Do not

scrub. Test in inconspicuous area with mild detergent prior to spot cleaning.





















#### COORDINATES COLLECTION



WIDTH 118"

COMPOSITION 100% Polyester

STANDARD ROLL LENGTH 33 LY (30m)

WEIGHT 9.72 oz/yd2 (329 g/m2) +/- 5%

THICKNESS 0.020" (0.51mm) +/- 5%

COLOR FASTNESS TO LIGHT 4.5 GRADE (AATCC 16-2003)

FIRE CLASSIFICATIONS CA U.S. Title 19; CAN/ULC-S109-14 Small Flame Test; NFPA701-2019 TM#1;

BS 5867:2008 Part 2:Type B

ANTI-MICROBIAL Bacterial Resistance: ASTM E2180; Fungal Resistance: ASTM G21, ASTM

G22, ECV

ENVIRONMENTAL GreenGuard, RoHS-Lead-Free, OEKO-TEX 100

ACOUSTIC PERFORMANCE N/A

CUTTING Cold, Ultrasonic, Crush or Laser

CARE INSTRUCTIONS Do not allow dust to accumulate. Regularly vacuum gently or use compressed

air. Use damp cloth only, do not allow shade to become fully wet. Do not

scrub. Test in inconspicuous area with mild detergent prior to spot cleaning.





















#### COORDINATES COLLECTION



WIDTH 118"

COMPOSITION 100% Polyester

STANDARD ROLL LENGTH 33 LY (30m)

WEIGHT 6.48 oz/yd2 ( 220 g/m2) +/- 5%

THICKNESS 0.016" (0.41mm) +/- 5%

COLOR FASTNESS TO LIGHT 4.5 GRADE (AATCC 16-2003)

FIRE CLASSIFICATIONS CA U.S. Title 19; CAN/ULC-S109-14 Small Flame Test; NFPA701-2019 TM#1;

BS 5867:2008 Part 2:Type B

ANTI-MICROBIAL Bacterial Resistance: ASTM E2180; Fungal Resistance: ASTM G21, ASTM

G22, ECV

ENVIRONMENTAL GreenGuard, RoHS-Lead-Free, OEKO-TEX 100

ACOUSTIC PERFORMANCE N/A

CUTTING Cold, Ultrasonic, Crush or Laser

CARE INSTRUCTIONS Do not allow dust to accumulate. Regularly vacuum gently or use compressed

air. Use damp cloth only, do not allow shade to become fully wet. Do not

scrub. Test in inconspicuous area with mild detergent prior to spot cleaning.





















#### COORDINATES COLLECTION



WIDTH 118"

COMPOSITION 100% Polyester

STANDARD ROLL LENGTH 33 LY (30m)

WEIGHT 10.90 oz/yd2 (369 g/m2) +/- 5%

THICKNESS 0.026" (0.65mm) +/- 5%

COLOR FASTNESS TO LIGHT 4.5 GRADE (AATCC 16-2003)

FIRE CLASSIFICATIONS CA U.S. Title 19; CAN/ULC-S109-14 Small Flame Test; NFPA701-2019 TM#1;

BS 5867:2008 Part 2:Type B

ANTI-MICROBIAL Bacterial Resistance: ASTM E2180; Fungal Resistance: ASTM G21, ASTM

G22, ECV

ENVIRONMENTAL GreenGuard, RoHS-Lead-Free, OEKO-TEX 100

ACOUSTIC PERFORMANCE N/A

CUTTING Cold, Ultrasonic, Crush or Laser

CARE INSTRUCTIONS Do not allow dust to accumulate. Regularly vacuum gently or use compressed

air. Use damp cloth only, do not allow shade to become fully wet. Do not

scrub. Test in inconspicuous area with mild detergent prior to spot cleaning.





















#### COORDINATES COLLECTION



WIDTH 118"

COMPOSITION 100% Polyester

STANDARD ROLL LENGTH 33 LY (30m)

WEIGHT 4.71 oz/yd2 (160 g/m2)

THICKNESS 0.014" (0.36mm) +/- 5%

COLOR FASTNESS TO LIGHT 4.5 GRADE (AATCC 16-2003)

FIRE CLASSIFICATIONS CA U.S. Title 19; CAN/ULC-S109-14 Small Flame Test; NFPA701-2019 TM#1;

BS 5867:2008 Part 2:Type B

ANTI-MICROBIAL Bacterial Resistance: ASTM E2180; Fungal Resistance: ASTM G21, ASTM

G22, ECV

ENVIRONMENTAL GreenGuard, RoHS-Lead-Free, OEKO-TEX 100

ACOUSTIC PERFORMANCE N/A

CUTTING Cold, Ultrasonic, Crush or Laser

CARE INSTRUCTIONS Do not allow dust to accumulate. Regularly vacuum gently or use compressed

air. Use damp cloth only, do not allow shade to become fully wet. Do not

scrub. Test in inconspicuous area with mild detergent prior to spot cleaning.

















