



MERMET E KOOLBLACK

SCREENS COLLECTION

1% | 3% | 5%

MERMET E KOOLBLACK

SCREENS COLLECTION



WIDTH	98", 122"
COMPOSITION	36% Fiberglass/64% Vinyl
OPENNESS FACTOR	1%, 3%, 5%
STANDARD ROLL LENGTH	30 LY (27m)
WEIGHT	1% - 12.95 oz/yd ² (439 g/m ²) +/- 5%; 3% - 11.3 oz/yd ² (382 g/m ²) +/- 5%; 5% - 10.6 oz/yd ² (358 g/m ²) +/- 5%
THICKNESS	1% - 0.021" (0.53mm) +/- 5%; 3% - 0.020" (0.51mm) +/- 5%; 5% - 0.019" (0.47mm) +/- 5%
COLOR FASTNESS TO LIGHT	8 GRADE (XENON-ARC-LAMP, BLUE SCALE)
FIRE CLASSIFICATIONS	CA U.S. Title 19; CAN/ULC-S109-03 Small & Large Flame Test; NFPA701-10 TM#1
ANTI-MICROBIAL	Bacterial Resistance: ASTM E2180; Fungal Resistance: ASTM G21
ENVIRONMENTAL	GreenGuard, GreenGuard Gold, RoHS-Lead-Free
ACOUSTIC PERFORMANCE	1% - NRC 0.50; SAA 0.47; 3% - NRC 0.35; SAA 0.33; 5% - NRC 0.10; SAA 0.12
CUTTING	Cold, Ultrasonic and Crush
CARE INSTRUCTIONS	Remove dust with vacuum cleaner or compressed air. Do not scrub. Do not use solvents or any abrasive substance which might damage the coating of the fabric. Clean with a sponge or soft brush dipped in soapy water using mild detergent. Rinse with clean water. Leave the shade down until completely dry. You can also very gently rub the fabric with a clean white pencil eraser to remove small stains.





MERMET M SCREEN

SCREENS COLLECTION

1% | 3% | 5%

MERMET M SCREEN

SCREENS COLLECTION



WIDTH	1% - 98", 122", 3% & 5% - 78", 98", 122"
COMPOSITION	36% Fiberglass/64% Vinyl
OPENNESS FACTOR	1%, 3%, 5%
STANDARD ROLL LENGTH	30 LY (27m)
WEIGHT	1% - 13.2 oz/yd ² (445 g/m ²) +/- 5%; 3% - 12.27 oz/yd ² (432 g/m ²) +/- 5%; 5% - 11.3 oz/yd ² (384 g/m ²) +/- 5%
THICKNESS	1% - 0.022" (0.56mm) +/- 5%; 3% - 0.022" (0.55mm) +/- 5%; 5% - 0.022" (0.55mm) +/- 5%
COLOR FASTNESS TO LIGHT	8 GRADE (XENON-ARC-LAMP, BLUE SCALE)
FIRE CLASSIFICATIONS	CA U.S. Title 19; CAN/ULC-S109-03 Small & Large Flame Test; NFPA701-10 TM#1
ANTI-MICROBIAL	Bacterial Resistance: ASTM E2180; Fungal Resistance: ASTM G21
ENVIRONMENTAL	GreenGuard, GreenGuard Gold, RoHS-Lead-Free
ACOUSTIC PERFORMANCE	1% - NRC 0.50; SAA 0.47; 3% - NRC 0.35; SAA 0.33; 5% - NRC 0.10; SAA 0.12
CUTTING	Cold, Ultrasonic and Crush
CARE INSTRUCTIONS	Remove dust with vacuum cleaner or compressed air. Do not scrub. Do not use solvents or any abrasive substance which might damage the coating of the fabric. Clean with a sponge or soft brush dipped in soapy water using mild detergent. Rinse with clean water. Leave the shade down until completely dry. You can also very gently rub the fabric with a clean white pencil eraser to remove small stains.

 Smarter Shades for
a Connected World.





Smarter Shades for
a Connected World.

OPACITY VISUALIZER

SCREENS COLLECTION

SIGNATURE SERIES BRITE WHITE/WHITE 1%

DAYTIME



NIGHTTIME



SIGNATURE SERIES BRITE WHITE/WHITE 3%

DAYTIME



NIGHTTIME



SIGNATURE SERIES BRITE WHITE/WHITE 5%

DAYTIME



NIGHTTIME



SIGNATURE SERIES BLACK/BLACK 1%

DAYTIME



NIGHTTIME



SIGNATURE SERIES BLACK/BLACK 3%

DAYTIME



NIGHTTIME



SIGNATURE SERIES BLACK/BLACK 5%

DAYTIME



NIGHTTIME



BASED ON

SIGNATURE SERIES



WIDTH	78.7", 98.4", 118"
COMPOSITION	24% Polyester/76% PVC
OPENNESS FACTOR	1%, 3%, 5%
STANDARD ROLL LENGTH	33 LY (30m)
WEIGHT	1% 14.57 oz/yd ² (494 g/m ²), 3% 13.93 oz/yd ² (472 g/m ²), 5% 12.71 oz/yd ² (431 g/m ²) +/- 5%
THICKNESS	1% 0.025" (0.63mm), 3% 0.024" (0.61mm) 0.023" (0.60mm) +/- 5%
COLOR FASTNESS TO LIGHT	8 GRADE (XENON-ARC-LAMP, BLUE SCALE)
FIRE CLASSIFICATIONS	CA U.S. Title 19; CAN/ULC-S109-14 Small Flame Test; NFPA701-2019 TM#1; BS 5867:2008 Part 2:Type B
ANTI-MICROBIAL	Bacterial Resistance: ASTM E2180; Fungal Resistance: ASTM G21, AATCC 30 PART 3
ENVIRONMENTAL	GreenGuard, GreenGuard Gold, RoHS-Lead-Free, REACH
ACOUSTIC PERFORMANCE	NRC 0.55; SAA 0.56 (ASTM C423)
CUTTING	Cold, Ultrasonic and Crush
CARE INSTRUCTIONS	Remove dust with vacuum cleaner or compressed air. Do not scrub. Do not use solvents or any abrasive substance which might damage the coating of the fabric. Clean with a sponge or soft brush dipped in soapy water using mild detergent. Rinse with clean water. Leave the shade down until completely dry. You can also very gently rub the fabric with a clean white pencil eraser to remove small stains.



Smarter Shades for
a Connected World.



**FADE
RESISTANT**



PVC FREE
ENVIRONMENTALLY
FRIENDLY



LEAD FREE
RoHS
COMPLIANT



**FLAME
RETARDANT**



**ROLL-A-SHADE®
WARRANTY**



ANTI-MICROBIAL



**UV
PROTECTION**




**ANTI
FUNGAL**



**NOISE
RESISTANT**



a product line of  **ROLL-A-SHADE®** 12101 Madera Way, Riverside CA 92503 951.245.5077



PHIFER SERIES 2500

SCREENS COLLECTION

1% | 3% | 5% | 10%

PHIFER SERIES 2500

SCREENS COLLECTION



WIDTH	63", 98", 126"
COMPOSITION	2500 - 37% Fiberglass 63% Vinyl on Fiberglass; 2410 - 36% Fiberglass 67% Vinyl on Fiberglass; 2390 - 35% Fiberglass 57% Vinyl on Fiberglass; 2360 - 35% Fiberglass 57% Vinyl on Fiberglass;
OPENNESS FACTOR	1%, 3%, 5%, 10%
STANDARD ROLL LENGTH	30 LY (27.4m)
WEIGHT	2500 - 16.2 oz/yd2 (549 g/m2) +/- 5%; 2410 - 14.1 oz/yd2 (478 g/m2) +/- 5%; 2390 - 11.8 oz/yd2 (400 g/m2) +/- 5%; 2360 - 10.4 oz/yd2 (353 g/m2) +/- 5%;
THICKNESS	2500 - 0.024" (0.61mm) +/- 5%; 2410 - 0.020" (0.51mm) +/- 5%; 2390 - 0.017" (0.43mm) +/- 5%; 2360 - 0.019" (0.48mm) +/- 5%;
COLOR FASTNESS TO LIGHT	8 GRADE (XENON-ARC-LAMP, BLUE SCALE)
FIRE CLASSIFICATIONS	CA U.S. Title 19; CAN/ULC-S109-14 Small Flame Test; NFPA701-2019 TM#1; BS 5867:2008 Part 2:Type B
ANTI-MICROBIAL	Bacterial Resistance: ASTM E2180; Fungal Resistance: ASTM G21, AATCC 30 PART 3, ASTM G22
ENVIRONMENTAL	GreenGuard, GreenGuard Gold, RoHS-Lead-Free, REACH
ACOUSTIC PERFORMANCE	2500 - NRC 0.55; SAA 0.54; 2410 - NRC 0.20; SAA 0.21; 2390 - NRC 0.10; SAA 0.12; 2360 - NRC 0.05; SAA 0.06;
CUTTING	Cold, Ultrasonic and Crush
CARE INSTRUCTIONS	Remove dust with vacuum cleaner or compressed air. Do not scrub. Do not use solvents or any abrasive substance which might damage the coating of the fabric. Clean with a sponge or soft brush dipped in soapy water using mild detergent. Rinse with clean water. Leave the shade down until completely dry. You can also very gently rub the fabric with a clean white pencil eraser to remove small stains.

 Smarter Shades for
a Connected World.





SIGNATURE SERIES

SCREENS COLLECTION

1% | 3% | 5%

SIGNATURE SERIES

SCREENS COLLECTION



WIDTH	78.7", 98.4", 118"
COMPOSITION	24% Polyester/76% PVC
OPENNESS FACTOR	1%, 3%, 5%
STANDARD ROLL LENGTH	33 LY (30m)
WEIGHT	1% 14.57 oz/yd ² (494 g/m ²), 3% 13.93 oz/yd ² (472 g/m ²), 5% 12.71 oz/yd ² (431 g/m ²) +/- 5%
THICKNESS	1% 0.025" (0.63mm), 3% 0.024" (0.61mm) 0.023" (0.60mm) +/- 5%
COLOR FASTNESS TO LIGHT	8 GRADE (XENON-ARC-LAMP, BLUE SCALE)
FIRE CLASSIFICATIONS	CA U.S. Title 19; CAN/ULC-S109-14 Small Flame Test; NFPA701-2019 TM#1; BS 5867:2008 Part 2:Type B
ANTI-MICROBIAL	Bacterial Resistance: ASTM E2180; Fungal Resistance: ASTM G21, AATCC 30 PART 3
ENVIRONMENTAL	GreenGuard, GreenGuard Gold, RoHS-Lead-Free, REACH
ACOUSTIC PERFORMANCE	NRC 0.55; SAA 0.56 (ASTM C423)
CUTTING	Cold, Ultrasonic and Crush
CARE INSTRUCTIONS	Remove dust with vacuum cleaner or compressed air. Do not scrub. Do not use solvents or any abrasive substance which might damage the coating of the fabric. Clean with a sponge or soft brush dipped in soapy water using mild detergent. Rinse with clean water. Leave the shade down until completely dry. You can also very gently rub the fabric with a clean white pencil eraser to remove small stains.

 Smarter Shades for
a Connected World.

