



# SIGNATURE 10% & HUSK II

## SHEER COLLECTION

# SIGNATURE 10% & HUSK II

## SHEER COLLECTION



|                         |   |
|-------------------------|---|
| WIDTH                   | SIGNATURE 10%: 78.7", 98.4", 118"   HUSK II: 114" (290 CM)  |
| COMPOSITION             | SIGNATURE 10%: 24% Polyester/76% PVC   HUSK II: 100% Polyester  |
| STANDARD ROLL LENGTH    | SIGNATURE 10%: 33 LY (30m)   HUSK II: 38 LY (35m)   |
| WEIGHT                  | SIGNATURE 10%: 11.65 oz/yd2 (395 g/m2) +/- 5%   HUSK II: 2.802 oz/yd2 (95 g/m2) +/- 5%  |
| THICKNESS               | SIGNATURE 10%: 0.022" (0.56mm) +/- 5%   HUSK II: 0.028" (0.7mm) +/- 5%  |
| COLOR FASTNESS TO LIGHT | SIGNATURE 10%: 8 GRADE (XENON-ARC-LAMP, BLUE SCALE)   HUSK II: 6 GRADE AS-2001.4.21   |
| FIRE CLASSIFICATIONS    | SIGNATURE 10%: CA U.S. Title 19; CAN/ULC-S109-14 Small Flame Test; NFPA701-2019 TM#1; BS 5867:2008 Part 2:Type B   HUSK II: N/A   |
| ANTI-MICROBIAL          | SIGNATURE 10%: Bacterial Resistance: ASTM E2180; Fungal Resistance: ASTM G21, AATCC 30 PART 3   HUSK II: N/A  |
| ENVIRONMENTAL           | SIGNATURE 10%: GreenGuard, GreenGuard Gold, RoHS-Lead-Free, REACH   HUSK II: Greenguard   |
| ACOUSTIC PERFORMANCE    | SIGNATURE 10%: NRC 0.55; SAA 0.56 (ASTM C423)   HUSK II: N/A  |
| CUTTING                 | SIGNATURE 10%: Cold, Ultrasonic and Crush   HUSK II: Ultrasonic   |
| CARE INSTRUCTIONS       | SIGNATURE 10%: Remove dust with vacuum cleaner or compressed air. Do not scrub. Do not use solvents or any abrasive substance which might damage the coating of the fabric. Clean with a sponge or soft brush dipped in soapy water using mild detergent. Rinse with clean water. Leave the shade down until completely dry. You can also very gently rub the fabric with a clean white pencil eraser to remove small stains. |

HUSK II: Do not allow dust to accumulate. Regularly vacuum gently or use compressed air. Use damp cloth only, do not allow shade to become fully wet. Do not scrub. Test in inconspicuous area with mild detergent prior to spot cleaning. Do not dry clean. Warm iron, if necessary.



**FADE  
RESISTANT**



**PVC FREE**  
ENVIRONMENTALLY  
FRIENDLY



**LEAD FREE**  
RoHS  
COMPLIANT



**FLAME  
RETARDANT**



**ROLL-A-SHADE®  
WARRANTY**



**PROTECTION**



**ANTI  
FUNGAL**



**NOISE  
RESISTANT**





# TOP ORIENT & PUGLIA

## SHEER COLLECTION

# TOP ORIENT & PUGLIA

## SHEER COLLECTION



|                         |  |
|-------------------------|--|
| WIDTH                   | ORIENT: 94" (240 CM)   PUGLIA: 110" (280CM)  |
| COMPOSITION             | 100% Polyester   |
| OPENNESS FACTOR         | N/A  |
| STANDARD ROLL LENGTH    | ORIENT: 43.76 LY (40m)   PUGLIA: 43.74 LY (40m)  |
| WEIGHT                  | ORIENT: 4.1 oz/yd <sup>2</sup> (140 g/m <sup>2</sup> ) +/- 5%   PUGLIA: 6.22 oz/yd <sup>2</sup> (211 g/m <sup>2</sup> ) +/- 5%   |
| THICKNESS               | ORIENT: 0.0177" (0.45mm) +/- 5%   PUGLIA: 0.0209" (0.53mm) +/- 5%  |
| COLOR FASTNESS TO LIGHT | ORIENT: 5+ DIN 150 105 - B02; DIN EN 410; DIN EN 13363-1   PUGLIA: 4-5 DIN ISO 105-B02   |
| FIRE CLASSIFICATIONS    | N/A  |
| ANTI-MICROBIAL          | N/A  |
| ENVIRONMENTAL           | ORIENT: Reach   PUGLIA: Greenguard, Reach  |
| ACOUSTIC PERFORMANCE    | N/A  |
| CUTTING                 | Ultrasonic   |
| CARE INSTRUCTIONS       | Do not allow dust to accumulate. Regularly vacuum gently or use compressed air. Use damp cloth only, do not allow shade to become fully wet. Do not scrub. Test in inconspicuous area with mild detergent prior to spot cleaning. Do not dry clean. Warm iron, if necessary. |



**FADE  
RESISTANT**



**PVC FREE**  
ENVIRONMENTALLY  
FRIENDLY



**LEAD FREE**  
RoHS  
COMPLIANT



**FLAME  
RETARDANT**



**ROLL-A-SHADE®  
WARRANTY**



**PROTECTION**